

GFS CG-670 Pump & Valve Packing

Braiding from a blend of carbon yarns

Description

Braided from a blend of carbon yarns, Style CG-670 is impregnated with a proprietary blocking agent, and high purity graphite flake. Designed to be highly durable and easy to install, Style CG-670 packing is also a low leakage, self lubricating packing. Our unique blend of Carbon yarns ensures extremely low shaft wear, while maintaining excellent heat dissipation. Typically used for severely caustic or corrosive media, this packing is suited for almost any high speed/high temperature pump or valve.

Construction:	Interlock Braid
Temperature Rating:	850°F / 455°C Air 1200°F / 649°C Steam 6000°F / 3315°C Non-Oxidizing Atmosphere
pH Rating:	0 - 14
Shaft Speed Rating:	4000 FPM / 20 MPS
Pressure Rating:	500 PSI / 34 Bar Pump 4350 PSI / 296 Bar Valve



Gallagher Fluid Seals, Inc.
500 Hertzog Blvd., King of Prussia, PA 19406
Phone: (610) 277-8200 | Fax: (610) 277-3850
www.gallagherseals.com
info@gallagherseals.com
The Seal Specialist

ISO
9001
2015
CERTIFIED

ISO
14001
2015
CERTIFIED